

PRESSURE TRANSMITTERS FOR LIQUIDS PTL SERIES



PTL series pressure transmitters are used for pressure detection in liquids in heating and cooling systems.

PTL-Heat is used for pressure detection in non-condensing applications, whereas PTL-Cool is designed for extreme conditions where condensation is a common problem. PTL-Cool has a two-layer protection for electronics. This is why the possible condensation does not harm the product.

PTL series products are also suitable for refrigerants and non-aggressive gases.



APPLICATIONS

PTL-Heat series devices are commonly used in HVAC/R systems for:

- Liquid heat exchangers
- Heating substation
- Air compressor systems

PTL-Cool series devices are commonly used in HVAC/R systems for:

- District cooling
- Fan coil units (FCU)
- Chilled beams

MODEL SUMMARY

Description	Model	Product code	Measurement range (bar)
PTL-Heat, for heating applications			
Pressure transmitter for liquids, voltage output	PTL-Heat-4-V	112.001.001	0...4 bar
Pressure transmitter for liquids, voltage output	PTL-Heat-6-V	112.002.001	0...6 bar
Pressure transmitter for liquids, voltage output	PTL-Heat-10-V	112.003.001	0...10 bar
Pressure transmitter for liquids, voltage output	PTL-Heat-16-V	112.004.001	0...16 bar
Pressure transmitter for liquids, voltage output	PTL-Heat-25-V	112.005.001	0...25 bar
Pressure transmitter for liquids, current output	PTL-Heat-4-A	112.001.002	0...4 bar
Pressure transmitter for liquids, current output	PTL-Heat-6-A	112.002.002	0...6 bar
Pressure transmitter for liquids, current output	PTL-Heat-10-A	112.003.002	0...10 bar
Pressure transmitter for liquids, current output	PTL-Heat-16-A	112.004.002	0...16 bar
Pressure transmitter for liquids, current output	PTL-Heat-25-A	112.005.002	0...25 bar
PTL-Cool, for cooling applications*			
Pressure transmitter for liquids, voltage output	PTL-Cool-6-V	112.002.005	0...6 bar
Pressure transmitter for liquids, voltage output	PTL-Cool-10-V	112.003.004	0...10 bar
Pressure transmitter for liquids, current output	PTL-Cool-6-A	112.002.006	0...6 bar
Pressure transmitter for liquids, current output	PTL-Cool-10-A	112.003.005	0...10 bar

*Other models available on request

PRESSURE TRANSMITTERS FOR LIQUIDS

PTL SERIES

SPECIFICATIONS

Performance

Accuracy (typ. %/FS):
(temperature: -20...85 °C)
±1.0 %

Overload range:
1.5 times full scale

Bursting pressure:
3.0 times full scale

Technical Specifications

Pressure type:

relative pressure

Measuring units:

bar

Environment:

Ambient temperature:

PTL-Heat: 0...105 °C, non-condensing

PTL-Cool: -40...60 °C

Temperature of medium:

PTL-Heat 0...85 °C

PTL-Cool: -40...50 °C

Physical

Measuring element:

Ceramic sensing element

Pressure connectors:

pressure G1/4", coupling G1/4"-G1/2"

Protection class:

IP65

PTL-Heat: one-layer protection

PTL-Cool: two-layer protection against condensation

Electrical

PTL with current output:

Supply voltage: 10...30 VDC

Output signal: 4...20 mA, max load 800 Ω / 24 VDC

PTL with voltage output:

Supply voltage: 15..24 VDC / 24 VAC (±10 %)

Output signal: 0...10 V, min load 5 kΩ

Conformance

Meets requirements for CE marking:

EMC Directive 2014/30/EU

RoHS Directive 2011/65/EU

WEEE Directive 2012/19/EU

COMPANY WITH
MANAGEMENT SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 = ISO 14001 =



HOW TO GENERATE A MODEL?

Example:	Product series			
	PTL-Heat-4-V	PTL-Heat	Pressure transmitters for liquids, for heating applications	
Measuring range (bar)				
-4			0...4	
-6			0...6	
-10			0...10	
-16			0...16	
-25			0...25	
Output				
		-V	Voltage	
		-A	Current	
Model	PTL-Heat	-4	-V	

Example:	Product series				
	PTL-Cool-6-V	PTL-Cool	Pressure transmitters for liquids, for cooling applications		
Measuring range (bar)					
-6			0...6		
-10			0...10		
Output					
				-V	Voltage
				-A	Current
Model	PTL-Cool	-6	-V		