

DIFFERENTIAL PRESSURE TRANSMITTERS DPT-PRIIMA SERIES

High accuracy, multi-range differential pressure transmitter for demanding applications



DPT-Priima is a high accuracy differential pressure transmitter designed for cleanrooms and other high accuracy applications. DPT-Priima has a new, extremely accurate sensor and automatic zero point calibration, optional span point calibration and calibration certificate.

DPT-Priima series devices include:

- Multiple measuring units, field selectable via jumper, including: Pa, kPa, mbar, inchWC, mmWC, psi.
- 8 field selectable measurement ranges, unidirectional or bi-directional, selectable via jumper, (see Model Summary).
- AZ (autozero) function for automatic zero point calibration, eliminating the need for periodic manual autozeroing to ensure long term accuracy.
- Proportional output options including: voltage (0/2-10 V) and current (4-20 mA).



DPT-Priima series device options offer:

- Backlit display
- Field adjustable span point calibration (i.e. gain)

SIMILAR PRODUCTS

- DPT-R8 series 8-range differential pressure transmitters
- DPT-2W series differential pressure transmitters with 4-20 mA 2-wire configuration
- DPT-MOD series differential pressure transmitters with Modbus configuration
- DPI series electronic differential pressure switches
- PS series mechanical differential pressure switches
- DPT-Flow series air flow transmitters

APPLICATIONS

DPT-Priima is commonly used in applications requiring high measurement accuracy:

- monitoring pressure in cleanrooms
- monitoring pressure difference across the building envelope
- monitoring pressure and flow

MODEL SUMMARY

Measurement ranges (Pa) (field selectable via jumper) (For optional units, see Specifications)	DPT-Priima ±25, ±50, ±100, ±500 0...25, 0...50, 0...250, 0...1000	
Description	Model	Product code
High accuracy differential pressure transmitter		
- with AZ	DPT-Priima-AZ	103.039.001
- with AZ & display	DPT-Priima-AZ-D	103.039.002
- with AZ & span point calibration	DPT-Priima-AZ-S	103.039.003
- with AZ, display & span point calibration	DPT-Priima-AZ-D-S	103.039.004
- with AZ & calibration certificate	DPT-Priima-AZ-C	103.039.005
- with AZ, display & calibration certificate	DPT-Priima-AZ-D-C	103.039.006
- with AZ, span point calibration & calibration certificate	DPT-Priima-AZ-S-C	103.039.007
- with AZ, display, span point calibration & calibration certificate	DPT-Priima-AZ-D-S-C	103.039.008

DIFFERENTIAL PRESSURE TRANSMITTERS

DPT-PRIIMA SERIES

SPECIFICATIONS

Performance

Measurement accuracy* (from applied pressure):

0.4 % ±0.4 Pa

(including: general accuracy, linearity, hysteresis, long term stability, and repetition error)

Output accuracy*:

Voltage: ± 0.025 V at 25 °C

Current: ± 0.04 mA typical, at 25 °C, load 100 Ω

± 0.1 mA max, at 25 °C, load 20–500 Ω

*after an half-hour warm-up time

Overpressure:

Proof pressure: 10 kPa

Burst pressure: 30 kPa

Zero point calibration:

Automatic autozero and manual pushbutton

Response time:

0.4 s or 8.0 s, selectable via jumper

(63 % of the change)

Technical Specifications

Media compatibility:

Dry air or non-aggressive gases

Measuring units:

Pa, kPa, mbar, inchWC, mmWC, psi, selectable via jumper

Measuring element:

MEMS, no flow-through

Environment:

Operating temperature: -5...50 °C,

Temperature compensated range 0...50 °C

Storage temperature: -40...70 °C,

Humidity: 0 to 95 % rH, non-condensing

Physical

Dimensions:

Case: 90.0 x 95.0 x 36.0 mm

Weight:

140g

Mounting:

2 each 4.3 mm screw holes, one slotted

Materials:

Case: ABS

Lid: PC

Duct connectors: ABS

Tubing: PVC

Protection standard:

IP54

Display (Optional)

2-line display (12 characters/line)

Line 1: active measurement

Line 2: units

Electrical connections:

4-screw terminal block

Wire: 0.2–1.5 mm² (12–24 AWG)

Cable entry: M16

Pressure fittings:

Male ø 5,2 mm

+ High pressure

- Low pressure

Electrical

Voltage:

Circuit: 3-wire (V Out, 24 V, GND)

Input: 24 VAC or VDC, ±10 %

Output: 0–10V / 2–10V

Power consumption: <1.0 W,

Resistance minimum: 1 kΩ

Current:

Circuit: 3-wire (mA Out, 24 V, GND)

Input: 24 VAC or VDC, ±10 %

Output: 4–20 mA

Power consumption: <1.2 W,

Maximum load: 500 Ω

Minimum load: 20 Ω

Conformance

Meets the requirements for CE marking:

EMC Directive 2014/30/EU

RoHS Directive 2011/65/EU

WEEE Directive 2012/19/EU

COMPANY WITH
MANAGEMENT SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 = ISO 14001 =



AZ-CALIBRATION

AZ-calibration is an autozero function in the form of an automatic zeroing circuit built into the PCB board. The AZ-calibration electronically adjusts the transmitter zero at predetermined time intervals (every 10 minutes). The AZ-calibration eliminates all output signal drift due to thermal, electronic or mechanical effects, as well as the need for technicians to remove high and low pressure tubes when performing initial or periodic transmitter zero point calibration.

The AZ adjustment takes 4 seconds. To avoid conflict with the BAS system, the output and display values will freeze to the latest measured value, after which the device returns to its normal measuring mode. Transmitters equipped with the AZ-calibration are virtually maintenance free.

HOW TO GENERATE A MODEL?

Example: DPT-Priima-AZ-D-S	Product series		Differential pressure transmitter			
	DPT	Model type				
		-Priima	High accuracy			
		Zero point calibration				
		-AZ	With autozero calibration			
		Display				
		-D	With display			
			Without display			
		Span point calibration				
		-S	Span point calibration			
	Without span point calibration					
Calibration certificate						
	-C	With calibration certificate				
		Without calibration certificate				
Model	DPT	-Priima	-AZ	-D	-S	